

**Listing of Claims:**

1. (currently amended) An adaptor for holding a surveillance camera inside a housing enclosure comprising ~~a pair of complementary~~ first and second interlocking shells for engagement around said camera, each such shell including a base, first and second  
5 sidewalls attached to said base, and an endwall attached to said base and extending between said sidewalls; said first shell having at least one locking tab on the outer edge of ~~said first a~~ said first sidewall thereof; and said second shell having at least one slot on the outer edge of ~~said second~~ a sidewall thereof such that the at least one tab of each of said first shell ~~sidewalls~~ engages the at least one slot of each of said second ~~sidewalls of the complementary~~ shell forming a single  
10 ~~rectangular unit for holding around~~ rectangular unit for holding around said camera.
2. (currently amended) The adaptor of claim 1 wherein a plurality of interior ridges are provided on ~~said the~~ the base and ~~each of said~~ each of said sidewalls of each of said shells forming a plurality of slots for holding PC boards associated with said camera.
3. (currently amended) The adaptor of claim 1 wherein a first outwardly  
15 extending tab is provided on ~~said the~~ the base of one of said shells at the corner where said base meets ~~said the~~ the first sidewall opposite from ~~said the~~ the endwall, and a second outwardly extending tab is provided on said base at the corner where said base meets ~~said the~~ the second sidewall opposite from ~~said the~~ the endwall.
4. (currently amended) The adaptor of claim ~~[[3]]~~ 10 wherein at least one  
20 mounting slot is provided in each of said outwardly extending tabs.

5. (currently amended) The adaptor of claim [[3]] 1 wherein at least one mounting opening is provided on the base of ~~each~~ at least one of said shells and on the first sidewall of each of said shells.

6. (currently amended) The adaptor of claim [[5]] 1 wherein an opening is  
5 provided on ~~each~~ at least one of said endwalls for communication between the interior and exterior of said unit.

7. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the base of ~~each~~ at least one of said shells for communication between the interior and exterior of said unit.

10 8. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the first sidewall of ~~each~~ at least one of said shells for communication between the interior and exterior of said unit.

9. (currently amended) The adaptor of claim [[6]] 1 wherein at least one opening is provided on the second sidewall of ~~each~~ at least one of said shells for  
15 communication between the interior and exterior of said unit.

10. (new) The adaptor of claim 3 wherein a third outwardly extending tab is provided on the base of the other of said shells at the corner where said base meets the first sidewall opposite from the endwall, and a fourth outwardly extending tab is provided on said base at the corner where said base meets the second sidewall opposite from the endwall.